

130W DC/DC Converter Dual Output Data Sheet



Description:

Green Watt Power’s 130W DC/DC power modules are designed with compact size, low cost, high efficiency and high reliability. Featured with a non-isolated mechanical structure and 12V/10A 5V/2A dual output, this series offers solid and safe power conversions on electric bike, electric motorcycle and other DC/DC applications.

- Wide Input Voltage: 36~92Vdc
- Output Voltage: 12Vdc & 5Vdc
- High Reliability
- Ultra-High Efficiency: Up to 96%
- Protection Features: SCP, Input UVP, Input Reverse Connection Protection
- Natural Cooling
- Operating Temperature: -20~60°C
- IP66 Ingress Grade



Module Number	Output Voltage	Maximum Output Current	Current Range	Voltage Range
EVD-60-130-D12-5 (PLD130-EVDO01-12)	12V	10A	0-8A	11.5V~12.5V
	5V	2A	0-2A	4.75V~5.15V

Input Parameters				
	Min	Typ	Max	Units
Input Voltage Range*	36	48/60	92	VDC
Input Current 36 VDC, Full Load 92 VDC, Full Load			5.5 2.5	A
Efficiency 36VDC Full Load 48VDC Full Load 60VDC Full Load	93.0 92.5 92.0	94.5 94.0 93.5		%

Output Parameters					
Output	Typical Load			Output Voltage Range	Output Voltage Ripple
Typ.	Min. Load	Full Load	Peak Load		
Output: 12V	0A	8A	10A	11.5V~12.5V	720mVp-p
Output: 5V	0A	2A	2A	4.75V~5.15V	300 mVp-p

General Specifications	
Output Short Circuit Protection	When its output is shorted, the power supply will enter hiccup mode, and will self-recover when the fault condition is removed.
Isolation	Non-isolation

Notes:

- (1) Specification is subject to change without notice.

Case Specifications:

Dimension: 85mm(L)*58mm(W)*21.5mm(H)

