

71-85W Li-Ion

- DC out 12~63V @ 1.35A - 4A
- AC in 90-264V
- Li-Ion Charger



215W Li-Ion

- DC out 26~54V @ 4.0A
- AC in 90-265V
- Li-Ion Charger



280W Li-Ion

- DC out 25~83V @ 3.5~6.6A
- AC in 90~265V
- Li-Ion Fully Sealed Battery Charger



600-700W Li-Ion

- DC out 30~84V @ 7.2~12A
- AC in 90~264V
- Li-Ion Battery Charger
- CAN Bus



720W Li-Ion

- DC out 69~116V @ 6.0A
- AC in 90~265V
- CAN Bus
- Li-Ion OBC, Fully Enclosed



750W Lead Acid

- DC out 22~30V @ 25A
- AC in 90~265V
- Lead-Acid Battery
- On-Board Charger



750W for 24V Li-Ion

- DC out 15~29.4V @ 25A
- AC in 90~265V
- Li-Ion Charger
- CAN Bus, IP65
- On/Off Board Charger



1kW Li-Ion

- DC out 40~84V @ 26A
- AC in 90~264V
- Li-Ion Battery Charger
- CAN Bus



1kW for 48/72V Li-Ion

- DC out 28~58.8V @ 18A or 43~86V @ 12A
- AC in 90~264V
- CAN Bus, IP67
- On/Off Board Charger



1.5/1.8kW 48/72V Li-Ion

- DC out 28~58.8V @ 25.5A or 43~86V @ 21.5A
- AC in 90~264V
- CAN Bus, IP67
- On/Off Board Charger



2.4kW for 48V Li-Ion

- 35~60VDC Out @ 40A
- 90~265VAC In
- Li-Ion High-Density
- CAN Bus
- J1772



3.3kW HV Li-Ion

- 200~420VDC Out @ 10A
- 90~265VAC In
- CAN Bus
- Li-Ion High-Density
- J1772



3.4kW for 72/84V Li-Ion

- 55~84VDC Out @ 40A
- 70~122V DC Out @ 34A
- 90~264V AC In
- CAN Bus
- J1772



3.5kW for 48V Li-Ion

- 35~60VDC Out @ 60A
- 90~264VAC In
- CAN Bus
- J1772
- IP66



6.6kW HV Liquid Cooled

- 200~420VDC Out @ 20A
- 90~265VAC In
- CAN Bus
- J1772
- IP67



7.2/9.5kW EVC Li-Ion

- DC out 0~90/100V @ 80/95A
- AC in 310~580V
- Li-Ion sealed High Density Charger
- CAN Bus



Non-isol. 94W Dual Out

- Non-isolated DC/DC
- Input: 36~72VDC
- Output A: 12V / 7A
- Output B: 5V / 1A
- Efficiency to 94%



Non-isol. 125W Dual Out

- Non-isolated DC/DC Module
- Input: 36~100VDC
- Output A: 12V/8A (10A peak)
- Output B: 5V / 2A
- IP65



Non-isol. 130W Dual Out

- Non-isolated DC/DC Module
- Input: 28~92V
- Output A: 12V / 10A
- Output B: 5V / 2A
- Efficiency to 96%



Non-isolated 200W

- Non-isolated DC/DC Module
- Input: 40~90V
- Output: 13.8V / 14A
- Enable Input
- IP65



Non-isolated 320W

- Non-isolated DC/DC Module
- Input: 28~160VDC
- Output: 24V @ 13.3A
- Efficiency to 95%
- On/Off control, IP65



48W isolated DC/DC

- Wide DC Input: 22~160V
- Output: 24V DC @ 2A
- Natural Cooling
- On/Off Control
- IP55



300W isolated DC/DC

- Input: 30~130 VDC
- Output: 13.2V@23A and 24V@125A
- IP67
- Molex or Flying lead



360W Isolated DC/DC

- Input: 100~400VDC
- Output: 5~48V @ 7.5~45A
- Efficiency to 95.5%
- AC input Optional



500W Isolated DC/DC

- Input: 30~130VDC
- Output: 13.5V @ 38A and 27.5V @ 18.5A
- IP67
- Molex or Flying lead



600W & 1kW Isolated

- Input: 280~420VDCV
- Output: 14V @ 43A & 72A
- Efficiency to 96%
- IP67



3~4.2kW Isolated DC/DC

- Input: 200~880VDC
- Output: 27.5~50.4V @ 62.5~110A
- Chill Plate or Heatsink
- Efficiency to 95.5%
- IP67



3kW Bi-Directional

- Bi-directional DC/DC Module
- In/Out: 270~420V & 10.5~14.5V
- Out: 14.5V @ 143A & 380V (Typ.) @ 11A
- Liquid Cooling / IP65



3kW~5kW Isolated

- Input: 400~650 VDC or 350~450 VDC
- Output: 32V @ 100A; 48V @ 70A/100A
- Output: 10~52V (Adjustable)



6.6kW/3.3kW Isolated

- DC/DC Module for Fuel Cells
- Input: 50~300 VDC
- Out: 300~450V @ 22A
- Smart Redundancy



10kW: Isolated

- DC/DC Converter (Low Profile)
- Input: 600~750 VDC
- Output: 50~560V (Adjustable)



66kW: Isolated

- Input: 50~300VDC
- Output: 300~450V @ 220A
- Smart Redundancy

